LNX000176 LINDA 70×80 *Linear pendant*



Recessed or surface-mounted linear LED luminaire. Dot-free light. Aluminium profile with diffusing screen. Paint finish according to RAL or NCS codes. Very high R9 index for naturally saturated red rendering.

PENDANT	IP 44 PROTECTION	CLASS I	≤ 43W/m POWER
3000K CCT	95 CRI	120° BEAM	Integrated DRIVER

CONTROL DALI

GENERAL

Category	Linear suspension
Environment	Indoor
IP rating	IP44
Installation	Recessed or surface-mounted
Power	Up to 43W/m
Colour temperature	3000K
Colour rendering (CRI)	Up to 95
Source flux	Up to 4680 Lm/m

OPTICS

Emission	Direct
LED source	High-quality LED strip
Distribution	Symmetric
Optics	Lambertian
Beam angle	120°

ELECTRICAL

Driver	Integrated
Power supply	220Vac
Insulation class	I


MECHANICAL

Dimensions	See drawing
Weight	4kg/m
Finish	Painted in RAL or NCS code
Material	Aluminium

TECHNICAL DRAWINGS AND DETAILS







NOTES

- Available in the following colour temperatures: 2700K, 3000K, 3500K, 4000K, 5000K, 6500K.
- Dimmable with integrated DALI driver.

ACCESSORIES AND OPTIONS

- Anti-glare filter available to control the UGR of the luminous flux.