ELVIS MENSOLA BIEMISSIONE *Wall light*



Fully customisable luminaire with direct/indirect emission source. Minimal design to optimise integration in historic and rustic residences with stone walls and wooden-beamed ceilings. Suitable for indoor wall installations. Indirect source: DALI/Push dimmable with integrated driver. Direct source: On/Off.

WALL	IP 40 PROTECTION	CLASS I	25W + 3W POWER
2700–4000K CCT	97 CRI	180° BEAM	Integrated DRIVER

CONTROL DALI Push

GENERAL

Category	Wall light
Environment	Indoor
IP rating	IP40
Installation	Wall/ceiling
Power	25W + 3W
Colour temperature	2700K,3000K,3500K,4000K
Colour rendering (CRI)	Up to 97
Source flux	3540Lm + 220Lm

OPTICS

Emission	Direct/indirect
LED source	COB LED
Distribution	Lambertian
Optics	PMMA diffuser
Beam angle	180°.

ELECTRICAL

Driver	Integrated
Power supply	220Vac
Insulation class	I

MECHANICAL

Dimensions	See drawing
Weight	700gr
Finish	Corten paint finish
Material	Aluminium, iron

NOTES

– Mechanical and electrical features can be customised according to the customer's wishes or needs.

TECHNICAL DRAWINGS AND DETAILS

