MONOLITH M + GROOVE *Projector*



Adjustable luminaire for ceiling cove installation, with a magnetic fixing system allowing completely free positioning. Tool-free adjustable pantograph orientation system. Gloss black painted collar for an anti-glare effect. Aluminium body, PMMA lens, direct light. Very high R9 value, for naturally saturated red colour rendering.

TRACK	IP 40 PROTECTION	CLASS III	16W POWER
3000K CCT	95 CRI	18° BEAM	Remote DRIVER

GENERAL

Category	Projector
Environment	Indoor
IP rating	IP40
Installation	On iron plate with magnets
Power	16W
Colour temperature	3000K
Colour rendering (CRI)	95
R9	97
Source flux	1795lm
Luminaire flux	See photometric data

OPTICS

Emission	Direct
LED source	COB
Distribution	Symmetric
Optics	PMMA lens, refractor
Beam angle	18°

ELECTRICAL

Driver	Remote
Power supply	500 mA
Insulation class	III

MECHANICAL

Dimensions	See drawing
Weight	0.47Kg
Finish	Raw aluminium, RAL 9005
Material	Aluminium, PMMA
Rotation	360°
Tilt	+/-90°

NOTES

- Dimmable with external remote constant current driver.
- Driver to be ordered separately.
- Available in the following colour temperatures: 2700K, 3000K, 3500K, 4000K, 5000K, 5700K, 6500K.
- Available with the following beam angles: 18°, 24°, 35°, 60°.

TECHNICAL DRAWINGS AND DETAILS

