MAXYSLASH 4X *Pendant downlight*



Custom linear luminaire, suitable for lighting large areas, high bay environments or hangars. Integrated drivers for direct 220Vac power supply. Standard suspension fixing. Fully customisable in size, power and finishes. High R9 index to enhance red rendering.

PENDANT	IP 20 PROTECTION	CLASS I	~110W POWER
4000K CCT	>90 CRI	30° BEAM	Integrated DRIVER

GENERAL

Category	Pendant downlight
Environment	Indoor
IP rating	IP20
Installation	Wall/ceiling
Power	~110W
Colour temperature	4000K
Colour rendering (CRI)	>90
Source flux	~15000lm
Luminaire flux	~12000lm

OPTICS

Emission	Direct
LED source	COB
Distribution	Symmetric
Optics	Reflectors
Beam angle	30°

ELECTRICAL


Driver	On board
Power supply	220Vac
Insulation class	I

MECHANICAL

Dimensions	See drawing
Weight	7Kg
Finish	Any RAL or NCS code
Material	Aluminium

TECHNICAL DRAWINGS AND DETAILS





NOTES

- Available optics: 15°, 30°, 60°.
- Available colour temperatures: 2700K, 3000K, 3500K, 4000K, 5000K, 6500K.
- CRI: up to 95.
- R9: up to 97.
- DALI dimmable on request.
- Made-to-measure bracket for surface mounting.