ARGE AERO M *Framing projector*



Framing projector suitable for art galleries, stage lighting and lighting effects. Equipped with adjustable and sliding framing shutters to optimise the framing of the images to be lit. Body painted according to RAL codes. Front lens group in black or white paint only. High CRI and R9 values for naturally saturated red colour rendering.

TRACK	IP 20 PROTECTION	CLASS II	10W POWER
4000K CCT	95 CRI	0–53° BEAM	Integrated DRIVER

GENERAL

Category	Framing projector
Environment	Indoor
IP rating	IP20
Installation	Surface-mounted or on EuroTrack
Power	10W
Colour temperature	4000K
Colour rendering (CRI)	95
Source flux	350 Lm

OPTICS

Emission	Direct
LED source	COB
Distribution	Spot
Optics	Framing projector
Beam angle	0° / 53°


ELECTRICAL


Driver	On board
Power supply	220Vac
Insulation class	II


MECHANICAL

Dimensions	See drawing
Weight	450gr
Finish	RAL and NCS paint finish
Material	Aluminium
Rotation	120°
Tilt	365°

TECHNICAL DRAWINGS AND DETAILS







NOTES

- Dimmable on request.
- Available in colour temperatures 2700K, 3000K, 4000K.
- Body colour available in all RAL finishes.
- Framing head available in black and white finish only.