OCULUS XS NAKED FL *Recessed downlight*



Trimless LED luminaire recessed in wooden panels.
Aluminium body, direct light.

RECESSED	IP 20 PROTECTION	CLASS III	5W POWER
2700K CCT	90 CRI	Remote DRIVER	

GENERAL

Category	Recessed downlight
Environment	Indoor
IP rating	IP20
Installation	Ceiling recessed
Power	5W
Colour temperature	2700K
Colour rendering (CRI)	90
Source flux	910lm (3000K) · 820lm (2400K)

OPTICS

Emission	Direct
LED source	COB LED
Distribution	Symmetric
Optics	Refractive
Beam angle	Medium

ELECTRICAL

Driver	Remote
Power supply	350mA
Insulation class	III

MECHANICAL

Dimensions	See drawing
Recess cut-out	30mm
Weight	400gr
Finish	RAL9001 - paintable
Material	Aluminium

NOTES

- Fully customisable luminaire.
- Note: insert the spotlight by screwing it in until it stops.
- Available in the following colour temperatures: 2700K, 3000K, 3500K, 4000K, 5000K, 5700K, 6500K.
- Available with the following beam angles: narrow, medium, wide.
- Installation on wood.
- The finish of the outer ring of the housing can be customised.

ACCESSORIES AND OPTIONS

- Optional: honeycomb anti-glare filter.

TECHNICAL DRAWINGS AND DETAILS









