SAGITTARIUS C TW *Soft panel*



350W LED softlight panel with variable white, pixel control and effects. Ultra-high-efficiency LED technology with a high colour rendering index, 96 Ra. Flood LEDs (110-degree beam angle) for a wider effective beam spread. Bi-colour function, colour temperature variable from 2700K to 6800K. Flicker-free dimming from 100% to 0%. Integrated DMX512 function with 3-pin XLR IN/OUT ports. RDM function for remote adjustment of settings. Ultra-quiet fan cooling, with fan speed adjustable via software.

PROJECTOR	IP 20 PROTECTION	CLASS II	350W POWER
10000K CCT	110° BEAM	Integrated DRIVER	

CONTROL DMX

GENERAL

Category	Soft panel
Environment	Indoor
IP rating	IP20
Installation	Bracket
Power	350W
Colour temperature	2700-10000K ± 100K
Colour rendering (CRI)	See photometric data
Luminaire flux	See photometric data

OPTICS

Emission	Direct
LED source	LED COB
Distribution	Symmetric
Optics	Lens
Beam angle	110°

ELECTRICAL

Driver	On board
Power supply	220~240V~50/60Hz
Insulation class	II

MECHANICAL

Dimensions	See drawing
Weight	11.000Kg
Finish	Black
Material	Aluminium
Rotation	+/- 360°
Tilt	+/- 360°

TECHNICAL DRAWINGS AND DETAILS



