AGAMAR M *Track projector*



Tiltable LED projector on mini track for general lighting. Aluminium body, PMMA lens. Paint finish according to RAL or NCS codes. Very high R9 value, for naturally saturated red colour rendering.

TRACK	IP 40 PROTECTION	CLASS III	12W POWER
3000K CCT	98 CRI	15° BEAM	Remote DRIVER

CONTROL · ON REQUEST **DALI**

GENERAL

Category	Track projector
Environment	Indoor
IP rating	IP40
Installation	Low-voltage miniaturised track
Power	12W
Colour temperature	3000K
Colour rendering (CRI)	98
R9	99
Source flux	1266Lm (3000K)
Luminaire flux	800Lm (3000K)

OPTICS

Emission	Direct
LED source	LED COB
Distribution	Symmetric
Optics	Refractive optics
Beam angle	15°


ELECTRICAL

Driver	Remote
Power supply	24Vdc
Insulation class	III

MECHANICAL

Dimensions	See drawing
Weight	350gr
Finish	Any RAL and NCS code
Material	Aluminium
Rotation	+/- 180°
Tilt	90°

TECHNICAL DRAWINGS AND DETAILS



NOTES

- Mechanical and optical features are fully customisable.
- Available in the following colour temperatures: 2700K, 3000K, 3500K, 4000K, 5000K, 5700K, 6500K.
- Available with the following beam angles: 15°, 25°, 40°.
- DALI 2 dimmable on request.
- Also available for installation on Nano track.

ACCESSORIES AND OPTIONS

- Optional: gloss black painted collar for anti-glare effect.
- Optional galvanic finishes (e.g. gold, nickel, burnishing).