NOVASPOT S 220VAC FL

Recessed and gimbal lights



Indoor LED luminaire for flush installation in false ceilings. The extremely slim body allows installation even in critical spots. Suitable for false ceiling installation using the supplied recessed housing. Magnetic fixing for quick installation. Anodised aluminium body, opal or satin PMMA cover. Integrated on-board 220Vac driver, eliminating the need for remote drivers. TRIAC dimmable.

RECESSED	IP 40 PROTECTION	CLASS I	4W POWER
4000K CCT	92 CRI	Integrated DRIVER	

CONTROL Triac

GENERAL

Category	LED
Environment	Indoor
IP rating	IP40
Installation	Recessed
Power	4W
Colour temperature	4000K
Colour rendering (CRI)	92
Source flux	500lm

OPTICS

Emission	Direct
LED source	LED array
Distribution	Symmetric
Optics	Acrylic refractive optics
Beam angle	Flood

ELECTRICAL

Driver	Integrated
Power supply	220 Vac
Insulation class	I

MECHANICAL

Dimensions	See drawing
Recess cut-out	Ø50
Weight	70g
Finish	Aluminium
Material	Aluminium

NOTES

- TRIAC dimmable.

ACCESSORIES AND OPTIONS

- Recessed housing with adjustable brackets to fit the false ceiling thickness.

TECHNICAL DRAWINGS AND DETAILS

