BULLET FL Q *Recessed and gimbal lights*



Fixed trimless LED luminaire, recessed with a square metal housing in false ceilings, furniture, shelves or displays. Aluminium body, PMMA lens, direct light. Very high R9 value, for naturally saturated red colour rendering.

RECESSED	IP 20 PROTECTION	CLASS III	5W POWER
3000K CCT	95 CRI	25° BEAM	Remote DRIVER

GENERAL

Category	LED
Environment	Indoor
IP rating	IP20
Installation	Ceiling recessed
Power	5W
Colour temperature	3000K
Colour rendering (CRI)	95
Source flux	600lm
Luminaire flux	See photometric data

OPTICS

Emission	Direct
LED source	LED COB o SMD
Distribution	Symmetric
Optics	Refractive optics
Beam angle	25°

ELECTRICAL

Driver	Remote
Power supply	300 mA
Insulation class	III

MECHANICAL

Dimensions	See drawing
Recess cut-out	42×42mm
Weight	80gr
Finish	Any RAL or NCS code
Material	Aluminium/PMMA

NOTES

- Dimmable with external remote constant current driver.
- Driver to be ordered separately.

- Available in the following colour temperatures: 2700K, 3000K, 3500K, 4000K, 5000K, 5700K, 6500K.
- Available with the following beam angles: 15°, 25°, 35°, 50°.
- Also available in a constant voltage version.
- Also available in a round version.

TECHNICAL DRAWINGS AND DETAILS

