NOVASIG *Recessed downlight*



Adjustable LED luminaire with trim, recessed in false ceilings with steel spring fixing. Aluminium body, PMMA lens, direct light.

RECESSED	IP 40 PROTECTION	CLASS III	15W POWER
3000K CCT	97 CRI	35° BEAM	Remote DRIVER

GENERAL

Category	Recessed downlight
Environment	Indoor
IP rating	IP40
Installation	Recessed in false ceiling
Power	15W
Colour temperature	3000K
Colour rendering (CRI)	97
Source flux	1290lm
Luminaire flux	See photometric data

OPTICS

Emission	Direct
LED source	COB LED
Distribution	Symmetric
Optics	PMMA lens, refractor
Beam angle	35°


ELECTRICAL

Driver	Remote
Power supply	350 mA
Insulation class	III

MECHANICAL

Dimensions	See drawing
Recess cut-out	See drawing
Weight	0.25Kg
Finish	White
Material	Aluminium
Rotation	360°
Tilt	+/-20°

TECHNICAL DRAWINGS AND DETAILS



NOTES

- Dimmable with external remote constant current driver.
- Driver to be ordered separately.
- Available in the following colour temperatures: 2700K, 3000K, 3500K, 4000K.
- Available with the following beam angles: 15°, 25°, 35°, 50°.