KIRK S LONG ARM *Track projector*

Fully customisable and adjustable LED luminaire for installation on low-voltage track. Aluminium body, PMMA lens. Direct light. Paint finish according to RAL and NCS codes. Very high R9 value for naturally saturated red colour rendering.



SURFACE	IP 40 PROTECTION	CLASS III	6W POWER
3000K CCT	98 CRI	25° BEAM	Remote DRIVER

GENERAL

Category	Track projector
Environment	Indoor
IP rating	IP40
Installation	Electrified track
Power	6W
Colour temperature	3000K
Colour rendering (CRI)	98
R9	97
Source flux	677Lm
Luminaire flux	See photometric data

OPTICS

Emission	Direct
LED source	COB LED
Distribution	Symmetric
Optics	PMMA lens, refractor
Beam angle	25°


ELECTRICAL

Driver	Remote
Power supply	24 Vdc
Insulation class	III

MECHANICAL

Dimensions	See drawing
Weight	0.16 Kg
Finish	RAL 9010 + gloss RAL 9005
Material	Aluminium
Rotation	360°
Tilt	+/- 90°

TECHNICAL DRAWINGS AND DETAILS



NOTES

- Tracks and drivers to be ordered separately.
- Mechanical and optical features are fully customisable on request.
- Available in the following colour temperatures: 2700K, 3000K, 3500K, 4000K, 5000K, 5700K, 6500K.
- Available with the following light beams: 15°, 25°, 40°, elliptical.

ACCESSORIES AND OPTIONS

- Optional: gloss black painted collar for anti-glare effect.