# NOVANOVA M PLA *Surface-mounted downlight*



Adjustable LED luminaire for surface installation. Aluminium body, PMMA lens, direct light. Suitable for installations with IP40 protection rating. Very high R9 value for naturally saturated red colour rendering.

| SURFACE | IP 40 | CLASS III | 10W |
|---|---|---|---|
| | PROTECTION | | POWER |
| **3000K** | **98** | **15°** | **Remote** |
| CCT | CRI | BEAM | DRIVER |



## GENERAL

| | |
|---|---|
| Category | Surface-mounted downlight |
| Environment | Indoor |
| IP rating | IP40 |
| Installation | Surface-mounted |
| Power | 10W |
| Colour temperature | 3000K |
| Colour rendering (CRI) | 98 |
| R9 | 97 |
| Source flux | 1055lm |
| Luminaire flux | See photometric data |

## OPTICS

| | |
|---|---|
| Emission | Direct |
| LED source | COB LED |
| Distribution | Symmetric |
| Optics | PMMA lens, refractor |
| Beam angle | 15° |


## ELECTRICAL

| | |
|---|---|
| Driver | Remote |
| Power supply | 600 mA |
| Insulation class | III |

## MECHANICAL

| | |
|---|---|
| Dimensions | See drawing |
| Weight | 0.35 kg |
| Finish | Anodised |
| Material | Aluminium |
| Rotation | 360° |
| Tilt | +/-25° |

### TECHNICAL DRAWINGS AND DETAILS




### NOTES

- Dimmable with remote external constant current driver.
- Integration of the driver inside the luminaire to be evaluated.
- Driver to be ordered separately.
- Available in the following colour temperatures: 2700K, 3000K, 3500K, 4000K, 5000K, 5700K, 6500K.
- Available with the following light beams: 15°, 35°, 60°.