NOVANOVA L PLA *Surface-mounted downlight*



Adjustable LED luminaire for surface installation. Aluminium body, PMMA lens, direct light. Suitable for installations with IP40 protection rating. Very high R9 value for naturally saturated red colour rendering.

SURFACE	IP 40 PROTECTION	CLASS III	18W POWER
3000K CCT	95 CRI	15° BEAM	Remote DRIVER

GENERAL

Category	Surface-mounted downlight
Environment	Indoor
IP rating	IP40
Installation	Surface-mounted
Power	18W
Colour temperature	3000K
Colour rendering (CRI)	95
R9	97
Source flux	1872lm
Luminaire flux	See photometric data

OPTICS

Emission	Direct
LED source	COB LED
Distribution	Symmetric
Optics	PMMA lens, refractor
Beam angle	15°


ELECTRICAL

Driver	Remote
Power supply	500 mA
Insulation class	III

MECHANICAL

Dimensions	See drawing
Recess cut-out	See drawing
Weight	0.45Kg
Finish	Anodised
Material	Aluminium
Rotation	360°
Tilt	+/-25°

TECHNICAL DRAWINGS AND DETAILS



NOTES

- Dimmable with remote external constant current driver.
- Integration of the driver inside the luminaire to be evaluated.
- Driver to be ordered separately.
- Available in the following colour temperatures: 2700K, 3000K, 3500K, 4000K, 5000K, 5700K, 6500K.
- Available with the following light beams: 15°, 35°, 60°.