SMART CANNON P-SHORT *Track projector*



Tiltable LED projector on Eurostandard track for general lighting. Aluminium body, PMMA lens. Paint finish according to RAL or NCS codes. Very high R9 value, for naturally saturated red colour rendering.

TRACK	IP 40 PROTECTION	CLASS II	25W POWER
3000K CCT	95 CRI	15–60° BEAM	Integrated DRIVER

GENERAL

Category	Track projector
Environment	Indoor
IP rating	IP40
Installation	Electrified Euro track
Power	25W
Colour temperature	3000K
Colour rendering (CRI)	95
R9	97
Source flux	2557Lm
Luminaire flux	See photometric data

OPTICS

Emission	Direct
LED source	LED COB
Distribution	Symmetric
Optics	Refractive and reflective optics (to be confirmed)
Beam angle	15°, 30°, 60°


ELECTRICAL

Driver	On board
Power supply	220 VAC
Insulation class	II

MECHANICAL

Dimensions	See drawing
Weight	300gr
Finish	RAL9005 + gloss RAL9005
Material	Aluminium
Rotation	359°
Tilt	0/90°

TECHNICAL DRAWINGS AND DETAILS







NOTES

- Mechanical and optical features are fully customisable.
- Available in the following colour temperatures: 2700K, 3000K, 3500K, 4000K, 5000K, 5700K, 6500K.

ACCESSORIES AND OPTIONS

- Optional: gloss black painted collar for anti-glare effect.
- Optional galvanic finishes (e.g. gold, nickel, burnishing).
- Optional: anti-glare honeycomb grid.
- Optional: barn doors.