ZUMY XS MILL DOUBLE *Track projector*



Adjustable, fully customisable LED luminaire for installation on low-voltage track. Aluminium body, PMMA lens, direct light. Paint finish according to RAL and NCS codes. Very high R9 value, for naturally saturated red colour rendering.

TRACK	PROTECTION	CLASS III	POWER
	IP 40		4.5W + 4,5W

CCT	CRI	DRIVER
3000K	98	Remote

CONTROL · ON REQUEST DALI

GENERAL

Category	Track projector
Environment	Indoor
IP rating	IP40
Installation	Electrified track
Power	4.5W + 4.5W
Colour temperature	3000K
Colour rendering (CRI)	98
R9	97
Source flux	564Lm + 564Lm
Luminaire flux	See photometric data

OPTICS

Emission	Direct
LED source	COB LED
Distribution	Symmetric
Optics	PMMA lens, refractor
Beam angle	Zoom


ELECTRICAL

Driver	Remote
Power supply	48 Vdc
Insulation class	III

MECHANICAL

Dimensions	See drawing
Weight	0.170 kg
Finish	RAL 9005
Material	Aluminium
Rotation	360°
Tilt	+/- 90°

TECHNICAL DRAWINGS AND DETAILS



NOTES

- Tracks and drivers to be ordered separately.
- Mechanical and optical features are fully customisable on request.
- DALI 2 dimmable on request.
- Available in the following colour temperatures: 2700K, 3000K, 3500K, 4000K, 5000K, 5700K, 6500K.