NONE NBS *Recessed downlight*



Tiltable LED luminaire for installation in backlit stretch ceilings, with adjustable metal recessed housing featuring a fabric locking function. Aluminium body, PMMA lens, direct light. Very high R9 value, for naturally saturated red colour rendering.

RECESSED	IP 40 PROTECTION	CLASS III	12W POWER
3000K CCT	98 CRI	24° BEAM	Remote DRIVER

GENERAL

Category	Recessed downlight
Environment	Indoor
IP rating	IP40
Installation	Recessed in stretch ceiling
Power	12W
Colour temperature	3000K
Colour rendering (CRI)	98
R9	97
Source flux	1266lm
Luminaire flux	See photometric data

OPTICS

Emission	Direct
LED source	COB LED
Distribution	Symmetric
Optics	PMMA lens, refractor
Beam angle	24°


ELECTRICAL

Driver	Remote
Power supply	700 mA
Insulation class	III


MECHANICAL

Dimensions	See drawing
Recess cut-out	Diam. 75mm on stretch ceiling
Weight	250gr
Finish	Anodised
Material	Aluminium
Rotation	360°
Tilt	+/-25°

TECHNICAL DRAWINGS AND DETAILS









NOTES

- Dimmable with external remote constant current driver (not included).
- Driver to be ordered separately.
- Available in the following colour temperatures: 2700K, 3000K, 3500K, 4000K, 5000K, 5700K, 6500K.
- Available with the following beam angles: 18°, 24°, 38°, 60°.