KIRK MAG

Surface-mounted and magnetic lights



Adjustable projector with high colour rendering COB LED source, adjustable on the x and y axes, with magnetic fixing for installation on an iron support and safety cable. Constant voltage powered, dimmable, compatible with DALI drivers. Available with honeycomb anti-glare filter. Also available in a track version.

MAGNETIC	IP 20 PROTECTION	CLASS III	6W POWER
2700–4000K CCT	98 CRI	18–40° BEAM	Remote DRIVER

CONTROL **DALI**

GENERAL

Category	LED
Environment	Indoor
IP rating	IP20
Installation	Magnetic
Power	6W
Colour temperature	2700K, 3000K, 3500K, 4000K
Colour rendering (CRI)	Up to 98
R9	Up to 97
Source flux	Up to 820Lm

OPTICS

Emission	Direct
LED source	LED COB
Distribution	Symmetric
Optics	Refractive PMMA
Beam angle	18°, 25°, 40°

ELECTRICAL


Driver	Remote
Power supply	24Vdc
Insulation class	III

MECHANICAL

Dimensions	See drawing
Weight	80gr
Material	Aluminium
Rotation	+/- 180°
Tilt	+50° -15°

TECHNICAL DRAWINGS AND DETAILS









NOTES

- Dimmable with driver not included.
- Also available with constant current driver.
- Mechanical and optical features are fully customisable on request.