CONTURAX 440 HIGH FLUX 220VAC DALI *Wall light*



Low-voltage fixed wall light in ribbed glass, with a custom design for decorative lighting in elegant settings, restaurants, shops, stairwells and homes. High-flux linear source to achieve high illuminance levels in indoor spaces. Suitable for wall installation with the dedicated bracket. Customisable in size, materials and finishes. On-board DALI dimmable driver.

WALL	IP 20 PROTECTION	CLASS I	16W POWER
3000K CCT	>90 CRI	360° BEAM	Integrated DRIVER

CONTROL DALI

GENERAL

Category	Wall light
Environment	Indoor
IP rating	IP20
Installation	Wall-mounted with bracket
Power	16W
Colour temperature	3000K
Colour rendering (CRI)	>90
Source flux	1850Lm

OPTICS

Emission	Wall light
LED source	High-flux LED strip
Distribution	Diffuse
Optics	Conturax glass diffuser
Beam angle	360°


ELECTRICAL


Driver	On-board driver
Power supply	220Vac
Insulation class	I

MECHANICAL

Dimensions	See drawing
Weight	3kg
Finish	Champagne-effect paint

TECHNICAL DRAWINGS AND DETAILS





NOTES

- Any RAL or NCS finish at no extra cost
- Galvanic finishes available.
- Available in brass or stainless steel.
- Available with IP65 protection rating.
- Available in CCT 2700K, 3000K, 4000K, 6500K.

ACCESSORIES AND OPTIONS

- Colour filters available to optimise lighting performance or for aesthetic needs