MONOLITH M PERISCOPE *Track projector*



Tiltable telescopic LED projector on magnetic track for general lighting. Telescopic joint to adapt its length to architectural needs. Gloss black painted collar for an anti-glare effect. Aluminium body, PMMA lens. Paint finish according to RAL or NCS codes. Very high R9 value, for naturally saturated red colour rendering.

TRACK	IP 20 PROTECTION	CLASS III	15W POWER
3500K CCT	97 CRI	25° BEAM	Remote DRIVER

GENERAL

Category	Track projector
Environment	Indoor
IP rating	IP20
Installation	48Vdc electrified mini track
Power	15W
Colour temperature	3500K
Colour rendering (CRI)	97
R9	98
Source flux	1615Lm
Luminaire flux	See photometric data

OPTICS

Emission	Direct
LED source	LED COB
Distribution	Symmetric
Optics	PMMA lens, refractor
Beam angle	25°


ELECTRICAL

Driver	Remote
Power supply	48 Vdc
Insulation class	III

MECHANICAL

Dimensions	See drawing
Weight	0.4 kg
Finish	White + gloss RAL 9005
Material	Aluminium
Rotation	360°
Tilt	+/- 90°

TECHNICAL DRAWINGS AND DETAILS



NOTES

- Mechanical and optical features are fully customisable.
- Available in the following colour temperatures: 2700K, 3000K, 3500K, 4000K, 5000K, 5700K, 6500K.
- Available with the following beam angles: 15°, 25°, 40°, 60°.