NABOO NAVY NIGHTHAWK *Downlight*



Fully customisable IP40 luminaire for panel installation, using a recessed housing with adjustable brackets to fit the panel thickness. Suitable for downlight use.

RECESSED	IP 40 PROTECTION	CLASS III	12W POWER
3000K CCT	90 CRI	25–60° BEAM	Remote DRIVER

GENERAL

Category	Downlight
Environment	Indoor
IP rating	IP40
Installation	On panel with recessed housing
Power	12W
Colour temperature	3000K
Colour rendering (CRI)	90
Source flux	2x(692lm at source)

OPTICS

Emission	Direct
LED source	Nichia
Distribution	Symmetric
Optics	Refractive optics
Beam angle	25°, 40°, 60°, diffuse

ELECTRICAL

Driver	Remote
Power supply	24Vdc
Insulation class	III

MECHANICAL

Dimensions	See drawing
Weight	200gr
Finish	Any RAL and NCS code
Material	Aluminium

NOTES

- All features are to be confirmed following analysis of prototypes or samples.
- Dimmable on request with external remote driver.
- Available in the following colour temperatures: 2500K, 2700K, 3000K, 3500K, 4000K, 5000K, 6500K.
- Painted in any RAL or NCS code at no extra charge.
- Galvanic finishes available at an extra charge, to be quoted.

TECHNICAL DRAWINGS AND DETAILS

