ORION XS PLA *Plate-mounted projector*



Very small adjustable outdoor LED projector with IP65 protection rating, for general outdoor architectural lighting installations. Suitable for installation in gardens, lawns, shrubs or outdoor paths. Aluminium body, glass cover, PMMA lens. Paint finishes according to RAL or NCS codes.

PROJECTOR	IP 65 PROTECTION	CLASS III	2W POWER
3000K CCT	90 CRI	20° BEAM	Remote DRIVER

GENERAL

Category	Plate-mounted projector
Environment	Outdoor
IP rating	IP65
Installation	On surfaces, with screws
Power	2W
Colour temperature	3000K
Colour rendering (CRI)	90
Source flux	112lm

OPTICS

Emission	Direct
LED source	LED Mid Power
Distribution	Symmetric
Optics	PMMA lens, refractor
Beam angle	20°

ELECTRICAL

Driver	Remote
Power supply	24 Vdc
Insulation class	III

MECHANICAL

Dimensions	See drawing
Weight	0.100Kg
Finish	Antique green
Material	Aluminium, tempered glass
Rotation	360°
Tilt	+/- 90°

NOTES

- Available with the following light beams: 15°, 20°, 25°, 38°, 60°, 20°x40°.
- Available in the following colour temperatures: 3000K, 4000K.
- Anti-glare snoot.
- Magnetic fixing plate.

TECHNICAL DRAWINGS AND DETAILS

