LINEAR DOUBLE DOT TRACK *Track projector*

Fully adjustable linear LED luminaire with a double row of light points for track installation. Aluminium body. On-board driver.



TRACK	PROTECTION	CLASS I	POWER
	IP 20		20W + 20W

CCT	CRI	BEAM	DRIVER
4000K	>95	40°	Integrated

CONTROL DALI Triac

GENERAL

Category	Track projector
Environment	Indoor
IP rating	IP20
Installation	Electrified track
Power	20W+20W
Colour temperature	4000K
Colour rendering (CRI)	>95
Source flux	3420Lm

OPTICS

Emission	Direct
LED source	LED COB
Distribution	Symmetric
Optics	Lens
Beam angle	40°

ELECTRICAL

Driver	On board
Power supply	220-240VAC 50/60Hz
Insulation class	I

MECHANICAL

Dimensions	See drawing
Weight	1.270Kg
Finish	Black
Material	Aluminium
Rotation	359°
Tilt	+/- 90°

NOTES

- On/Off with integrated driver.
- TRIAC, DALI, 0-10V on request.
- Available in the following colour temperatures: 2700K, 3000K, 4000K, 5000K, 6500K, Tunable White.
- Also available with 20° and 60° optics.

TECHNICAL DRAWINGS AND DETAILS





