KOR P *In-ground recessed*



IP65 in-ground recessed LED step light with dual asymmetric emission, for architectural lighting applications. Supplied with recessed housing as an installation accessory. Suitable for lighting parking areas. Suitable for through-wiring in-out electrical connection.

WALL	IP 65 PROTECTION	CLASS III	≤ 8W POWER
3000K CCT	90 CRI	Remote DRIVER	

GENERAL

Category	In-ground recessed
Environment	Outdoor
IP rating	IP65
Installation	Ground or wall installation
Power	Up to 8W
Colour temperature	3000K
Colour rendering (CRI)	90
Source flux	Up to 860lm

OPTICS

Emission	Step light
LED source	SMD
Distribution	Asymmetric
Optics	Opal diffuser
Beam angle	Wide + narrow

ELECTRICAL

Driver	Remote
Power supply	24Vdc
Insulation class	III

MECHANICAL

Dimensions	See drawing
Recess cut-out	See drawing
Weight	350gr
Finish	Any RAL or NCS code
Material	Aluminium

NOTES

- Dimmable with external driver to be ordered separately.
- Available in the following colour temperatures: 2700K, 3000K, 3500K, 4000K, 5000K, 6500K.
- Available with custom galvanic finishes or AISI 316L stainless steel flange for saline environments, quoted separately.

TECHNICAL DRAWINGS AND DETAILS

