EARTH S+ 220VAC *Ground projector*



Fixed luminaire with IP65 protection rating and plastic recessed housing for integration into concrete floors. Uplight beam with recessed anti-glare light source. Suitable for ground installation in outdoor areas. Aluminium body, tempered glass and steel flange. Direct light. On-board driver.

GROUND	IP 65 PROTECTION	CLASS I	6W POWER
3000K CCT	90 CRI	30° BEAM	Integrated DRIVER

CONTROL DALI Triac

GENERAL

Category	Ground projector
Environment	Indoor and outdoor
IP rating	IP65
Installation	Ground installation
Power	6W
Colour temperature	3000K
Colour rendering (CRI)	90
Source flux	750lm

OPTICS

Emission	Direct
LED source	LED Mid Power
Distribution	Symmetric
Optics	PMMA lens, refractor
Beam angle	30°

ELECTRICAL

Driver	On board
Power supply	230 VAC
Insulation class	I

MECHANICAL

Dimensions	See drawing
Recess cut-out	See drawing
Weight	1 Kg
Finish	Black and stainless steel
Material	Aluminium, PMMA, stainless steel, glass

NOTES

– On/Off, Triac, with integrated driver.

– DALI, with remote driver.

TECHNICAL DRAWINGS AND DETAILS

