NOVA NOVA L FL *Recessed downlight*



Adjustable trimless LED luminaire, recessed in false ceilings with metal recessed housing. Aluminium body, PMMA lens, direct light. Very high R9 value, for naturally saturated red colour rendering.

RECESSED	IP 40 PROTECTION	CLASS III	18W POWER
3000K CCT	95 CRI	24° BEAM	Remote DRIVER

GENERAL

Category	Recessed downlight
Environment	Indoor
IP rating	IP40
Installation	Recessed in false ceiling
Power	18W
Colour temperature	3000K
Colour rendering (CRI)	95
R9	97
Source flux	1872lm
Luminaire flux	See photometric data

OPTICS

Emission	Direct
LED source	COB LED
Distribution	Symmetric
Optics	PMMA lens, refractor
Beam angle	24°


ELECTRICAL

Driver	Remote
Power supply	500 mA
Insulation class	III

MECHANICAL

Dimensions	See drawing
Recess cut-out	See drawing
Weight	350gr
Finish	Anodised
Material	Aluminium
Rotation	360°
Tilt	+/-25°

TECHNICAL DRAWINGS AND DETAILS



NOTES

- Dimmable with external remote constant current driver.
- Driver to be ordered separately.
- Available in the following colour temperatures: 2700K, 3000K, 3500K, 4000K, 5000K, 5700K, 6500K.
- Available with the following beam angles: 15°, 24°, 35°.