
FUNNEL S+ ADJ *Recessed and gimbal lights*





Adjustable recessed LED spotlight for general lighting. Aluminium body. Fully customisable on request. IP65 protection rating, suitable for damp environments.

RECESSED	IP 40 PROTECTION	CLASS III	7.3W POWER
2700K CCT	>90 CRI	24° BEAM	Remote DRIVER

GENERAL

Category	COB LED
Environment	Indoor
IP rating	IP40
Installation	Ceiling or false ceiling
Power	7.3 W
Colour temperature	2700K
Colour rendering (CRI)	>90
Luminaire flux	690 lm

OPTICS

Emission	Direct
LED source	LED COB
Distribution	Symmetric
Optics	Spot
Beam angle	24°

ELECTRICAL

Driver	Remote
Power supply	200mA
Insulation class	III

MECHANICAL

Dimensions	See drawing
Recess cut-out	See drawing
Weight	250gr
Finish	All RAL and NCS codes
Material	Aluminium
Rotation	+/-180°
Tilt	+/-30°

NOTES

- Dimmable with remote constant current driver.
- Made-to-measure finishes available to match the ceiling finish.

ACCESSORIES AND OPTIONS

- Optional anti-glare honeycomb grid.

TECHNICAL DRAWINGS AND DETAILS

