AGAMAR XXS MILL MAG

Adjustable magnetic projector



Very compact and minimal adjustable surface-mounted LED projector for general lighting installations. Rear magnets allow easy fixing and positioning of the spotlight. Aluminium body, PMMA lens. Inner baffle finished in matt black to minimise the outer halo on the lit surface. Recessed light source for an anti-glare experience. The luminaire is designed to easily house different types of filters, even simultaneously, such as colour correction filters, beam softening filters and anti-glare filters.

MAGNETIC	IP 40 PROTECTION	CLASS III	4,5W POWER
3000K CCT	95 CRI	15° BEAM	Remote DRIVER

GENERAL

Category	Adjustable magnetic projector
Environment	Indoor
IP rating	IP40
Installation	On ferromagnetic surfaces
Power	4.5W
Colour temperature	3000K
Colour rendering (CRI)	95
R9	97
Source flux	564Lm (3000K)
Luminaire flux	See photometric data

OPTICS

Emission	Direct
LED source	LED COB
Distribution	Symmetric
Optics	Acrylic refractive optics
Beam angle	15°

ELECTRICAL

Driver	Remote
Power supply	220mA
Insulation class	III

MECHANICAL

Dimensions	See drawing
Weight	90gr
Finish	Any RAL or NCS code
Material	Aluminium
Rotation	0-90°
Tilt	+/- 180° Honeycomb accessory

TECHNICAL DRAWINGS AND DETAILS

