
NOVASPIRIT 1614 *Recessed linear*



Fully customisable linear LED luminaire, recessed in showcases, displays and furniture. Available in made-to-measure lengths. Continuous line light beam. Aluminium body, PMMA lens, direct light. Dimmable.

LINEAR	IP 40 PROTECTION	CLASS III	9.6W/m POWER

2700K CCT	94 CRI	Remote DRIVER

GENERAL

Category	Recessed linear
Environment	Indoor
IP rating	IP40
Installation	Recessed in shelves
Power	9.6W/m
Colour temperature	2700K
Colour rendering (CRI)	94
Source flux	898Lm/m

OPTICS

Emission	Direct
LED source	COB LED
Distribution	Wide
Optics	Refractive PMMA lens


ELECTRICAL

Driver	Remote
Power supply	24Vdc
Insulation class	III

MECHANICAL

Dimensions	See drawing
Recess cut-out	See drawing
Weight	0.15Kg/m
Finish	Natural anodised
Material	Aluminium, PMMA

TECHNICAL DRAWINGS AND DETAILS



NOTES

- All features are to be confirmed following prototype analysis.
- Dimmable on request with external remote driver.
- Driver to be ordered separately.
- The luminaire must be powered every two and a half metres.
- Mechanical and optical features are fully customisable on request.
- Available in the following colour temperatures: 2700K, 3000K, 3500K, 4000K, 5000K.
- Mechanical fixing.