NOVASPOT MJ RGBWW IP67 *Downlight*

Fixed watertight RGBW recessed spotlight with aluminium body and flange. DMX controllable. Driver and controller to be quoted separately: DMX driver and controller are remote and cannot be integrated into the spotlight.



RECESSED · IP 67 PROTECTION · CLASS III · 8W POWER

RGBWW COLOUR · 38° BEAM · Remote DRIVER

CONTROL DMX

GENERAL

Category	Downlight
Environment	Outdoor
IP rating	IP67
Installation	Ceiling recessed
Power	8W
Colour temperature	R, G, B, W 2700/3200K
Source flux	R 160Lm @ 700mA · G 310Lm @ 700mA · B 46Lm @ 700mA · W 260Lm @ 700mA

OPTICS

Emission	Direct
LED source	RGBW Star
Distribution	Symmetric
Optics	Colour-mixing refractive optics (to be confirmed)
Beam angle	38°


ELECTRICAL

Driver	Remote
Power supply	Up to 700mA
Insulation class	III

MECHANICAL

Dimensions	Ø80×51mm
Recess cut-out	Ø68mm
Weight	200gr
Finish	RAL9005
Material	Aluminium

TECHNICAL DRAWINGS AND DETAILS



NOTES

- Dimmable with constant current driver not included.
- Remote driver to be selected according to the architectural design and the number of projectors to be controlled.
- Fully customisable luminaire: all technical features can be modified on request according to the needs of the project manager or client.